

Lieutenant Governor

State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER

Executive Director

Division of Oil, Gas and Mining JOHN R BAZA

Division Director

Reviewed



Inspection Report Minerals Regulatory Program

Date Submitted:

08/06/2013

Mine Name: Black Shale/Rose Mine		Permit Number:	M/049/0084	4 Permit	Fees:	Paid
Operator Name: Interstate Brick Co.		Inspection Date:	Inspection Date: 08/06/201		Bond Amount:	
Inspector(s): A. Abate, J. Hewitt, Frankie		Time:	11:00 AM	Bond Escalation:		due \$182,000
Othe	ers:	Mine Status:	Proposed			
Elements of Inspection				Evaluated	Comment	Enforcement
1.	Permits, Revisions, Transfer, Bonds			V	✓	
2.	Public Safety (shafts, adits, trash, signs, highwalls)			V	V	
3.	Protection of Drainages/Erosion Control					
4.	Deleterious Material			V	V	
5.	Roads (maintenance, surfacing, dust control, safety)					
6.	Reclamation					
7.	Backfilling/Grading (trenches, pits, roads, highwalls, shafts)			V	V	
8.	Soils					
9.	Revegetation			V	V	

Purpose of Inspection

This large mine operation was recently approved to transition from a small mine permit to a large mine permit. This site incorporates the Rose Mine - a pre-law site that will be incorporated into this large mine permit. The purpose of this inspection was to familiarize myself with the new large mine site.

Inspection Summary

Both the Black Shale and the Rose mine were pre-law mines that Interstate Brick is planning to reactivate. More recently, the Rose mine was permitted under Exploration Permit E/49/0051. The Division has granted tentative approval contingent upon the end of a 30 day public comment period. The tentative approval was granted on July 15, 2013. The public comment period will end on August 15, 2013. Several topsoil piles were surprisingly salvaged by the previous operator. The current operator will utilize these topsoil piles during reclamation. A considerable amount of trash items used for target practice was in the pit areas. One of the pits contains a seep where tamerisk was seen on the highwall. Water from a contact between the shale layer and the underburden is where the seep daylights. The groundwater from the seep drains to the pit. The operator has dug a trench along the road to prevent water from flooding the road into the mine. The highwall of the pits were not terraced and do not appear to be safe. OGM requires that highwalls not be greater than a 45 degree angle. The operator indicated that mining will begin next spring.

Conclusions and Recommendations

In accordance with rule R647-4-107.1.14, the operator should install a gate where public access to the site is readily available.

Inspector's Signature:

CC: John Hewitt, Interstate Brigk Co. -9780 S 5200 W, West Jordan, UT 84088


File: /C/Documents and Settings/AprilAbate/Desktop/Black Shale -Insp-08062013.pdf



Mine: M/049/0084 Inspected: 08/06/2013




Entry into the Black Shale Mine. A considerable amount of debris was noted in the pit.



The rocky outcrop area on the top of the hill is the pre-law area where mining initially took place.




One of the topsoil piles salvaged at the base of the pit.




Highwall of pit that will be mined. Tamerisk in the background is the location of the groundwater seep.



Mine: M/049/0084 Inspected: 08/06/2013








Evidence of flooding based on the mudcracks. The operator plans to retain this feature as a pond to promote wildlife habitat.



Topsoil pile to the left of the photo.



View of the Rose mine on the other side of the ridge. The operator plans to mine this concurrently with the Black Shale mine.

